

c. Amendments to Claims

1. (currently amended) An apparatus comprising:

a delta-sigma analog-to-digital converter for converting an analog input signal, comprising:

an analog band-pass loop filter configured to filter an analog signal derived from the analog input signal, the loop filter having a center band-pass frequency; and

a quantizer configured to produce a series of digital signals by sampling the filtered analog signal from the loop filter at a sampling frequency, ~~and~~ wherein the series of digital signals has a data-carrying frequency spectrum that is a mirror image of a data-carrying frequency spectrum of the analog input signal, the data-carrying spectrum of the series being located between the center band-pass frequency and zero; and

~~wherein the a digital-to-analog converter is configured to generate a series of the analog feedback signals at the sampling frequency and with~~ such that each analog feedback signal has a duty cycle of less than $\frac{1}{2}$ and corresponds to one of the digital signals.

2. (original) The apparatus of claim 1, wherein the sampling frequency is f_s , the center band-pass frequency of the loop filter is f_c , and $f_s = (4/3) f_c \pm 10\%$.

3. (original) The apparatus of claim 1, wherein the loop filter has an order of four or higher.

4. (original) The apparatus of claim 1, further comprising a digital demodulator being coupled to receive the digital signals and configured to remove frequencies above a lower edge of the loop filter's band-pass frequency.

5. (currently amended) The apparatus of claim 1,

~~wherein the delta-sigma analog-to-digital converter further comprises:~~

~~a digital-to-analog converter configured to generate a series of analog feedback signals, each analog feedback signal corresponding to one of the digital signals; and~~

~~wherein the analog band-pass loop filter is configured to filter the analog signal~~

derived from the analog input signal by sequentially combining the analog feedback signals with the analog input signal.

6. (original) The apparatus of claim 5, wherein the loop filter has an order that is higher than two.

7 – 8. (canceled)

9. (currently amended) The apparatus of claim 1, wherein the digital-to-analog converter is configured to produce the analog feedback signals in a return-to-zero format.

10. (original) The apparatus of claim 7, wherein the digital-to-analog converter is configured to produce the analog feedback signals with duty cycles of less than about 1/3.

11. (currently amended) A method, comprising:

transmitting an analog input signal having a data-carrying band to a delta-sigma ~~ADC~~ analog-to-digital converter to convert the analog input signal into a series of digital signals having a data-carrying band, ~~the transmitting including~~ ;

filtering ~~the~~ a modified analog ~~input~~ signal with a loop band-pass filter having a center band-pass frequency; and

wherein the series of digital signals has a data-carrying frequency spectrum that is a mirror image of a data-carrying frequency spectrum of the analog input signal, the data-carrying spectrum of the series being located between the center band-pass frequency and zero; and

~~wherein the transmitting further comprises:~~

performing digital-to-analog conversions of the digital signals to sequentially produce analog feedback signals with duty cycles of less than 1/2; and

producing the modified analog signal ~~transmitted to the loop filter~~ by sequentially combining the analog feedback signals with the analog input signal.

12. (currently amended) The method of claim 11, further comprising;

sampling the filtered modified analog ~~input~~ signal to produce the digital signals at a sampling frequency.

13. (original) The method of claim 12, wherein the sampling frequency is f_s , a center band-pass frequency of the loop filter is f_c , and $f_s = (4/3) f_c \pm 10\%$.

14. (original) The method of claim 12, wherein the loop filter has an order of four or higher.

15. (previously presented) The method of claim 11, further comprising:
filtering the digital signals with a digital demodulator whose band pass is configured to remove frequencies higher than a lower edge of the loop filter's band pass.

16 – 17. (canceled)

18. (currently amended) The method of claim ~~[[16]]~~ 11, wherein the act of performing produces the analog feedback signals with duty cycles of less than 1/3.

19. (previously presented) The method of claim 11, wherein the act of performing produces the analog feedback signals in a return-to-zero format.